



Fresh air for your kitchen

The 6000 ExtractionTech Hood contains a powerful, efficient motor allowing you to clear your kitchen environment of fumes and cooking odours without waiting.

Product Benefits & Features

Clean air. Faster.

This Cooker hood clears the kitchen from cooking fumes quickly. That is because the advanced cooker hood has an efficient and powerful motor.

- Installation type: Pull-out, width 60 cm
- Recirculatory intensive: 490 m³/h
- Power settings in recirculation mode (high/low): 448 / 205 m³/h
- Electronic push buttons control with 3+Intensive speeds
- Electronic Regulation
- Number of speeds: 3+Intensive
- Light Temperature, K
- Watt Volt
- Grease filter type and number: Aluminium mesh, 2
- Supercharcoal Filter: SUPCHARCE1, 902 979 622
- Super performing filter regenerative after 2 hours in oven at 150°C
- Super performing filter life ca. 3-4 years
- Maximum noise level (high/low): / dB(A)

LEDlights for more refined cooking

Our LEDlights use far less energy than other lights, with a much longer life expectancy. And they provide expert illumination for greater detail while cooking.



Maximum filtration, again and again

A highly functioning filter that captures and removes fats and odours when cooking. The removable filter can be cleaned in the dishwasher, ensuring that your cooker hood is continually efficient.

One Touch. Complete Control

The full range of hood functions are consolidated into a single electronic control. Meaning settings can be monitored and adjusted with just one touch. Precisely and intuitively.

Product Specification

Product Number Code	942 150 551	Sound power min speed, dB(A)	46
EAN	7332543520541	Recirculation Intensive, m³/h	490
EPRELRegCode	86974	Recirculation Max, m³/h	448
Annual Energy consumption, KWh/annum	39.7	Recirculation Min, m³/h	205
Energy Efficiency class	A	Recirc. sound power max, dB(A)	70
Fluid dynamic efficiency class	A	Recirc. sound power min, dB(A)	51.3
Fluid dynamic efficiency index	33.5	LightTemperature	3000
Lighting efficiency class	E	Remote control	Not available
Lighting efficiency index	9	Minimum distance from cooking top ELECTRIC	43
Grease filter efficiency class	D	Minimum distance from cooking top GAS	65
Grease filter efficiency index	66	Weight gross cleaner and accessories with packaging	12.5
Height max. external	395	Weight net cleaner and accessories no packaging	10.9
Width mm	598	Package heigth	511
Depth mm	280	Package width	693
Air outlet	150	Package depth	396
Main colour	Grey	Weight package Corrugated Cardboard	1400
Charcoal filter type	MCFE18	Weight package PE	38
Charcoal filter PNC	902 980 119	Weight package Polystyrene (EPS/EPP)	280
Voltage	220-240	Country of origin	IT
Capacity intensive, m³/h	647		
Capacity, Max m³/h	537		
Capacity, Min m³/h	256		
Sound power intensive, dB(A)	67		
Sound power max speed, dB(A)	63		

