



Dry Natural. Easy

The new AirDry technology will easily dry your dishes with natural airflows. The dishwasher door opens up 10 cm in the last part of the program so when you are ready to unload your dishes they will be clean and dry. All natural.

Product Benefits & Features

An intensive programme for conveniently clean

The intensive programme in our dishwasher uses a powerful 70°C jet of water to easily remove even the most stubborn residue. Cleaning all your dishes thoroughly so they're ready to use again straight from a cycle.

Just 30 minutes to completely clean

Our dishwasher features a fast-wash programme that cleans light loads quickly and thoroughly in just half an hour. So your dishes are ready to use at a moment's notice.

Set the dishwasher to start when it suits

The delay function lets you start your dishwasher cycle at a time that's convenient – whether three, six or nine hours ahead. Meaning you can clean dishes when it suits you and unload them when you have the time or energy. It's ideal for taking advantage of off-peak rates, or running a programme when hot water isn't required

A perfect fit with Sliding Hinge

PerfectFit Sliding Hinge makes installing your new dishwasher a breeze. The system is so adaptable it can fit all niche machine heights and removes the need to cut the plinth. Total dishwasher integration with genuine ease.

- Water sensor detects the level of dirt and adjusts water consumption
- LED display
- AutoOff
- Warm water 60°C
- 5 programmes, 4 temperatures
- Dishwasher programmes: AUTO Wash 45°-70°, Eco 50°, Glass 45°, Intensive 70°, Quick Wash 60°
- Options: XtraDry
- Delay start options: 3h/6h/9h
- Buzzer
- Inverter motor
- Height adjustable upper basket, even when fully loaded
- Upper basket with
- Cutlery basket
- Lower basket with 2 foldable plate racks
- Aqua Control
- Panel with symbols
- Indication for salt refill

Product Specification

Product Number Code	911 535 200	Weight gross cleaner and accessories with packaging	35.82
Bar code	7332543554935	Weight net cleaner and accessories no packaging	34.3
EnergyClassE20	F	Package heigth	864
EnergyCons100CycleE20	0	Package width	635
WaterConsE20	0	Package depth	680
NoisedBAE20	0		
OffModePwE20	0		
StandByPwE20	0		
DelayStartE20	0		
Installation in height	None		
Installation	FI		
Inlet hose type of	Aqua control		
Anti-flood device	Floating switch		
Water supply	Cold or hot		
Panel colour	Black		
Required fuse (A)	10		
Connected load (W)	1950		
Voltage	220-240		
Cord length external	1.5		
Height total	818		
Width mm	596		
Depth mm	550		
Built in depth mm	550		
Built in height (min), mm	820		
Built in width mm	600		

